

DD IEC/PAS 62611:2009



BSI Standards Publication

Vacuum cleaners for commercial use – Methods for measuring performance

bsi.

...making excellence a habit.™

This is a preview. [Click here to purchase the full publication.](#)

National foreword

This Draft for Development is the UK implementation of IEC/PAS 62611:2009.

This publication is not to be regarded as a British Standard.

It is being issued in the Draft for Development series of publications and is of a provisional nature. It should be applied on this provisional basis, so that information and experience of its practical application can be obtained.

A PAS is a Technical Specification not fulfilling the requirements for a standard, but made available to the public and established in an organization operating under a given procedure.

A review of this Draft for Development will be carried out not later than three years after its publication.

Notification of the start of the review period, with a request for the submission of comments from users of this Draft for Development, will be made in an announcement in the appropriate issue of Update Standards. According to the replies received, the responsible BSI Committee will judge whether the validity of the PAS should be extended for a further three years or what other action should be taken and pass their comments on to the relevant international committee.

Observations which it is felt should receive attention before the official call for comments will be welcomed. These should be sent to the Secretary of the responsible BSI Technical Committee at British Standards House, 389 Chiswick High Road, London W4 4AL.

The UK participation in its preparation was entrusted by Technical Committee CPL/59, Performance of household electrical appliances, to Subcommittee CPL/59/6, Floor treatment appliances.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© BSI 2009

ISBN 978 0 580 65710 8

ICS 97.080

Compliance with a British Standard cannot confer immunity from legal obligations.

This Draft for Development was published under the authority of the Standards Policy and Strategy Committee on 31 October 2009

Amendments issued since publication

Amd. No.	Date	Text affected
----------	------	---------------



PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

Vacuum cleaners for commercial use – Methods for measuring performance

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XB**

ICS 97.080

ISBN 2-8318-1042-2

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references	9
3 Terms and definitions	9
4 General conditions for testing.....	11
4.1 Atmospheric conditions	11
4.2 Test equipment and materials.....	12
4.3 Voltage and frequency	12
4.4 Running-in of vacuum cleaner and attachments	12
4.5 Equipment of the vacuum cleaner.....	12
4.6 Operation of the vacuum cleaner.....	13
4.7 Conditioning prior to tests.....	13
4.8 Initial application of dust.....	13
4.9 Mechanical operator.....	13
4.10 Number of samples	13
4.11 In-house reference cleaner system(s).....	13
5 Dry vacuum cleaning tests.....	14
5.1 Dust removal from hard flat floors.....	14
5.1.1 Test equipment.....	14
5.1.2 Test area and stroke length	14
5.1.3 Removal of remaining dust	14
5.1.4 Distribution of test dust.....	14
5.1.5 Preconditioning of dust receptacle	14
5.1.6 Determination of dust removal ability	15
5.2 Dust removal from hard floors with uneven surfaces.....	15
5.2.1 Test equipment.....	15
5.2.2 Distribution of test dust.....	15
5.2.3 Determination of dust removal ability	15
5.3 Dust removal from carpets.....	16
5.3.1 Test carpet	16
5.3.2 Test area and stroke length	16
5.3.3 Conditioning of test carpet.....	17
5.3.4 Distribution of test dust.....	17
5.3.5 Embedding of dust into carpet	17
5.3.6 Preconditioning of dust receptacle	17
5.3.7 Determination of dust removal ability	18
5.4 Dust removal along walls.....	19
5.4.1 Test equipment and materials.....	19
5.4.2 Distribution of test dust.....	19
5.4.3 Determination of dust removal ability along walls.....	19
5.5 Fibre removal from carpets.....	20
5.6 Maximum usable volume of the dust receptacle.....	20
5.6.1 Conditions for measurement.....	20

5.6.2	Introduction of moulding granules	20
5.6.3	Determination of maximum usable volume of dust receptacle	20
5.7	Air data	20
5.7.1	Conditions for measurement	21
5.7.2	Test equipment	21
5.7.3	Determination of air data	21
5.8	Performance with loaded dust receptacle	22
5.8.1	Determination of suction pressure change with loaded dust receptacle	22
5.8.2	Throttling to simulate loaded dust receptacle	25
5.8.3	Determination of performance with loaded dust receptacle	26
5.9	Filtration efficiency of the vacuum cleaner	26
5.9.1	Test conditions	26
5.9.2	Determining the test dust quantity	26
5.9.3	Test procedure	26
5.9.4	Evaluation	27
5.9.5	Particle concentration and dilution	29
5.9.6	Record keeping	29
5.10	HEPA filtration equivalence of the vacuum cleaner	30
5.10.1	Object of the test	30
5.10.2	Test procedure	30
5.10.3	Determination of HEPA equivalence	30
5.11	Total emissions of the vacuum cleaner	30
5.11.1	Test method	30
6	Miscellaneous tests	30
6.1	Motion resistance	31
6.1.1	Test carpet and test equipment	31
6.1.2	Determination of motion resistance	31
6.2	Cleaning under office furniture	31
6.2.1	Distribution of test dust	32
6.2.2	Determination of free office furniture height	32
6.3	Maximum radius of operation	32
6.3.1	Conditions for measurement	32
6.3.2	Determination of radius of operation	32
6.4	Impact resistance	32
6.4.1	Test equipment	33
6.4.2	Determination of impact resistance	33
6.5	Deformation of hose and connecting tubes	33
6.5.1	Test equipment	33
6.5.2	Determination of permanent deformation	33
6.6	Bump test	34
6.6.1	Test equipment	34
6.6.2	Test cycle	35
6.6.3	Test procedure	36
6.7	Flexibility of the hose	36
6.7.1	Preparation of test object	36
6.7.2	Determination of the flexibility of the hose	37
6.8	Repeated bending of the hose	37

6.8.1	Test equipment.....	37
6.8.2	Test method	38
6.9	Life test.....	38
6.10	Mass	39
6.11	Weight in hand	39
6.12	Dimensions	39
6.13	Noise level	39
6.14	Energy consumption.....	39
6.14.1	Energy consumption when vacuuming of carpets.....	39
6.14.2	Energy consumption with vacuuming of hard floors with uneven surfaces	41
7	Test material and equipment	42
7.1	Material for measurements	42
7.1.1	Test carpets	42
7.1.2	Standard dust type	43
7.1.3	Fibre material	45
7.1.4	Moulding granules	45
7.2	Equipment for measurements	45
7.2.1	Floor test plate	45
7.2.2	Test plates with uneven surfaces.....	45
7.2.3	Carpet-beating machine	45
7.2.4	Carpet hold-downs and guides	46
7.2.5	Dust spreader.....	47
7.2.6	Rollers for embedding	47
7.2.7	Equipment for air data measurement	48
7.2.8	Test equipment for determining the fractional filtration efficiency of the vacuum cleaner	52
7.2.9	Device for motion resistance test.....	54
7.2.10	Device for impact test.....	54
7.2.11	Device for determination of deformation of hoses and connecting tubes	55
7.2.12	Mechanical operator	56
7.2.13	Weighing machine	57
8	Instructions for use.....	57
9	Information at the point of sale	58
Annex A (informative)	Information on materials.....	59
Annex B (informative)	Information at the point of sale	62
Annex C (informative)	Information on materials.....	63
Bibliography.....		65
Figure 1 – Right-angled T		19
Figure 2 – Air data curves.....		22
Figure 3a – Connecting tube openings.....		23
Figure 4 – Test dust for loading dust receptacle.....		24
Figure 5 – Dust spread uniformly on surface		25
Figure 6 – Insertion depth.....		32
Figure 7 – Position of test object and cross-section for measurement of deformation.....		34

Figure 8a – Profile of threshold	35
Figure 8b – Arrangements for bump test	35
Figure 9 – Preparation of hoses for testing flexibility	37
Figure 10 – Equipment for repeated bending of hoses	38
Figure 11 – Grain size diagram for test dust.....	44
Figure 12 – Carpet-beating machine	46
Figure 13 – Carpet hold-downs and guides	46
Figure 14 – Dust spreader and roller for embedding dust into carpets	47
Figure 15a – Alternative A equipment for air data measurements.....	48
Figure 15b – Measuring box for alternative A	49
Figure 15c – Alternative B equipment for air data measurements	50
Figure 15 – Alternative A and B	50
Figure 16 – Drum for impact test.....	55
Figure 17 – Device for testing deformation of hoses and connecting tubes.....	56
Figure 18 – Mechanical operator for the measurement of dust removal from carpets and of motion resistance	57
 Table 1 – Confidence limits of a Poisson distribution for 95 % – confidence range	 29