

- b) illustrations shall be used wherever possible; and
- c) instructions shall include at least the following information:
 - 1) details of the installation, operation, inspection and maintenance of the equipment;
 - 2) clause or note drawing the operator's attention to the need to increase inspection/maintenance if the equipment is subject to heavy use and/or the stability of the equipment relies on one post;
 - 3) advice to take care, in relation to specific hazards to children, due to incomplete installation or dismantling, or during maintenance.

The manufacturer/supplier should supply copies of test reports to purchasers upon request.

6.1.2 Pre-information

The manufacturer/supplier shall provide information concerning the safety of the installation prior to the acceptance of the order, e.g. a catalogue data sheet.

This information shall include at least the following, where relevant:

- a) minimum space;
- b) surfacing requirements (including free height of fall and extent of surfacing);
- c) details of the foundations and any specific provisions for their accessibility during inspection and maintenance;
- d) overall dimensions of the largest part(s);
- e) mass of the heaviest part/section in kilograms;
- f) guidance regarding the target user group for the equipment;
- g) if the equipment is intended only for indoor use or under supervised conditions;
- h) availability of spare parts; and
- i) certification of conformity with this European Standard.

6.1.3 Installation information

The manufacturer/supplier shall supply an equipment delivery parts list with the equipment.

The manufacturer/supplier shall supply installation instructions for the correct assembly, erection and placing of the equipment.

This information shall include at least the following:

- a) minimum space requirements and safety clearances;
- b) equipment and parts identification;
- c) erection sequence (assembly instruction and installation details);
- d) matching aids where necessary, e.g. signs on parts accompanied by appropriate instructions;

- e) need for any special tools, lifting devices, templates or other assembly aids to be used and any precautionary measures to be taken. Where necessary, torque values should be given;
- f) constructional space required to install the item of equipment;
- g) orientation, where necessary, in relation to sun and wind;
- h) details of the required foundation, under normal conditions, anchorage in the ground and the design and location of the foundation (with a note that care should be taken concerning abnormal conditions);
- i) details of the foundations and any specific provisions for their accessibility during inspection and maintenance;
- j) specific instructions if a particular landscape profile is necessary for safe operation, e.g. falling height;
- k) free height of fall (for impact attenuation surfacing needs);
- l) need for and details of the application of any painting or treatment: and
- m) removal of assembly aids before the equipment is used.

Drawings and diagrams shall clearly specify the principal dimensions of the equipment and the relevant space, heights and areas required for installation.

The manufacturer/supplier shall supply the details necessary for inspection^{N6)} of the playground equipment prior to its first use.

6.1.4 Inspection and maintenance information

NOTE Attention is drawn to EN 1176-7.

6.1.4.1 The manufacturer/supplier shall provide instructions for maintenance (marked with the number of this standard), which shall include a statement that the frequency of inspection will vary with the type of equipment, e.g. equipment where the stability relies on one post, or materials used and other factors, e.g. heavy use, levels of vandalism, coastal location, air pollution, age of equipment.

The manufacturer/supplier shall also provide drawings and diagrams necessary for maintenance, inspection and checking of correct operation and, when appropriate, repair of the equipment.

6.1.4.2 The instructions shall specify the frequency with which the equipment or its components should be inspected or maintained and shall include guidance on the following, where relevant:

- a) routine visual inspection (see 3.26);

NOTE 1 For playgrounds subject to heavy use or vandalism, daily inspection of this type might be necessary.

NOTE 2 Examples of visual and operational inspection points are: cleanliness, equipment ground clearances, ground surface finishes, exposed foundations, sharp edges, missing parts, excessive wear (of moving parts) and structural integrity.

- b) operational inspection (see 3.27);

This should be done every 1 to 3 months, or as indicated by the manufacturer's instruction.

N6) National footnote: "Inspection" means the acceptance inspection of the equipment.

Special attention should be given to 'sealed-for-life' parts and equipment where stability relies on one post.

- c) annual main inspection (see 3.28).

Special attention should be given to 'sealed-for-life' parts and equipment where stability relies on one post.

NOTE 3 The annual main inspection may require excavation or dismantling of certain parts.

6.1.4.3 The instructions shall also specify the following:

- a) if necessary, the servicing points and methods of servicing, e.g. lubrication, tightening of bolts, re-tensioning of ropes;
- b) that replacement parts shall conform to manufacturer's specifications;
- c) if special disposal treatment is required for some equipment or parts;
- d) identification of spare parts;
- e) any additional measures to be taken during the run-in period, e.g. tightening of fastenings, tensioning of ropes;
- f) the need to keep drainage holes clear;
- g) that surfacing shall be maintained: in particular, the levels of loose fill materials.
- h) that GRP (glass-reinforced plastics) should be replaced or repaired before the glass fibres become exposed through wear or damage. This particularly applies to slides.

6.2 Information to be provided by the manufacturer or supplier of impact attenuating surfacing

6.2.1 Pre-information for impact attenuating surfacing

The manufacturer/supplier shall provide the following information concerning the performance of the impact attenuating surfacing prior to the acceptance of the order (does not apply to turf/topsoil):

- a) where particulate materials that are included in Table 4 are specified, clear information about the type of material (see Table 4) and the depth of the layer to be used shall be provided, or, if not included in Table 4, the critical fall height of the surfacing as tested in accordance with EN 1177, together with copies of test reports or certificates;
- b) outline of the installation procedure, climatic limitations on installation and other precautions required;
- c) procedures to be followed for the operation, inspection and maintenance of the surfacing;
- d) factors that could affect the properties of the impact attenuating surfacing in service;
- e) period for which the adequate level of impact attenuation is expected with adequate maintenance;
- f) how the material allows for routine inspection of equipment foundations, particularly where one-post equipment is to be surrounded by wet pour/poured-in place material;

- g) whether the material is intended for indoor or outdoor use, or both;
- h) availability of spare parts (if any) and methods to be used for the repair of localized areas of damage;
- i) compliance of impact attenuating surfacing materials with 4.1 (namely 4.1.6), if applicable;
- j) a note drawing the operator's attention to the need to increase the frequency of inspection/maintenance if the impact attenuating surfacing is subject to heavy use and/or any conditions that could reduce the impact attenuation (e.g. degradation of organic materials or vandalism as well as influence of ageing due to UV exposure);
- k) a warning to take care, in relation to specific hazards to children, during incomplete installation or during maintenance.

6.2.2 Installation information for impact attenuating surfacing

The manufacturer/supplier of playground surfacing shall provide full and detailed installation instructions in the appropriate language(s) of the country in which the surfacing is to be installed and used. These instructions shall conform to the following:

- a) instructions shall be printed legibly and in a simple form;
- b) illustrations shall be used wherever possible; and
- c) instructions shall include at least the following information:
 - 1) complete procedure for the preparation of the ground, substrate, drainage, etc.;
 - 2) assembly and installation details for the surfacing and equipment required to ensure that the adequate level of impact attenuation is provided;
 - 3) how to deal with edges, perimeters and junctions with other materials, if necessary;
 - 4) any weather limitations during the installation and any subsequent weather protection required;
 - 5) specific instructions if a particular landscape profile is necessary for safe installation and performance;
 - 6) conditions to meet impact attenuation surfacing needs according to the free height of fall of the equipment.

The manufacturer/supplier shall supply the details necessary for inspection of the playground impact attenuating surfacing prior to its first use.

6.2.3 Inspection and maintenance information for impact attenuating surfacing

NOTE Attention is drawn to EN 1176-7.

6.2.3.1 The manufacturer/supplier of playground surfacing shall provide instructions for maintenance and inspection procedures, e.g. removal of contaminants, with a statement that the frequency of inspection will vary with the type of impact attenuating surfacing material used and its surroundings, e.g. access/exit areas, and other factors, e.g. heavy use, levels of vandalism, coastal location, air pollution, ageing of material.

NOTE Lack of maintenance can reduce the impact attenuation properties.

6.2.3.2 Maintenance instructions shall provide all information necessary for retaining the required performance (e.g. minimum depth of particulate impact attenuating surfacing) and, when appropriate, repair or refill of the impact attenuating surfacing. For all types of impact attenuating surfacing particular attention shall be given to the effects of ageing (exposure to UV, heat, cold), pollution, causing degradation or the loss of impact attenuating properties.

The instructions shall also specify the following:

- a) that replacement parts shall conform to manufacturer's specifications;
- b) if special disposal treatment is required for the material or parts;
- c) the identification of spare parts (connectors, slabs, ...);
- d) any additional measures to be taken, specifically methods of cleaning, disinfecting, repairing etc.;
- e) the need to keep drainage system functioning;
- f) that surfacing shall be maintained: in particular, the depth of loose fill materials.

NOTE The annual main inspection may require excavation and access to foundations and subsequent repair of the impact attenuating surfacing.

6.2.4 Identification of impact attenuating playground surfacing

The surfacing shall be labelled by the manufacturer or supplier, or written information shall be provided for its identification and performance.

7 Marking

7.1 Equipment identification

The equipment shall be marked legibly, permanently and in a position visible from ground level with at least the following:

- a) name and address of manufacturer or authorized representative;
- b) equipment reference and year of manufacture; and
- c) the number and date of this European Standard, i.e. EN 1176-1:2017.

7.2 Basic level mark

Equipment shall be marked legibly and permanently with the basic level mark (see Figure 24).

Annex A **(normative)**

Loads

A.1 Permanent loads

A.1.1 General

Loads “Q” (in Newtons) on equipment and equipment elements are created by the gravity (g) of masses ($Q = G \times g$; masses “G” in kg) as well as by dynamic effects of these masses (e.g. from swings), but also from connected elements (e.g. ropes, chains) and from external influences (e.g. wind). The calculation of the total loads (forces “F” and “T” in Newtons) and their combination, acting on different examples of equipment, is described in the following clauses.

For static analysis (stress-calculations) in load bearing parts of equipment the safety factors for the loads as given in B.2 shall be used.

The permanent loads (Q_p) consist of:

- a) loads created by the mass of self-weight of the structure and of the assemblies (Q_p);
- b) pre-stressing loads, e.g. space nets, cableways (Q_t); and
- c) loads created by the mass of water if any water containers are involved (Q_p).

A.1.2 Loads created by self-weight

Loads created by the mass of self-weight of the structure and assemblies shall be assessed.

A.1.3 Pre-stressing loads

Pre-stressing loads are considered to be permanent loads. The maximum and minimum pre-stressing loads have to be considered.

NOTE Because of creep or relaxation, pre-stress is time dependent. It could be necessary to verify two situations:

- a) initial pre-stress; and
- b) end pre-stress.

A.1.4 Mass of water

The highest and lowest possible water levels in the container shall be considered.

A.2 Variable loads

A.2.1 General

The variable loads (Q_i) consist of:

- a) user loads;

- b) snow loads;
- c) wind loads;
- d) temperature loads; and
- e) specific loads.

A.2.2 User loads

The loads resulting from users of playground equipment shall be based on the following load system:

- a) total mass

$$G_n = n \times m + 1,64 \times \sigma \sqrt{n} \quad (\text{A.1})$$

where

- G_n is the total mass of n children, in kilograms;
- n is the number of children on the equipment or part thereof, as given in A.3;
- m is the mean mass of a child in a specified age group;
- σ is the standard deviation of the age group concerned.

For open public and private playgrounds the following values can be used:

$$m = 53,8 \text{ kg}$$

$$\sigma = 9,6 \text{ kg}$$

These values are based on data for children of 14 years of age. However the calculated loads include safety factors, which ensure structures may also be used by adults.

For playgrounds with supervision open to well-defined age groups only (e.g. day-care centres), the following values can be used:

- age up to 4 years: $m = 16,7 \text{ kg}$ $\sigma = 2,1 \text{ kg}$;
- age up to 8 years: $m = 27,9 \text{ kg}$ $\sigma = 5,0 \text{ kg}$;
- age up to 12 years: $m = 41,5 \text{ kg}$ $\sigma = 7,9 \text{ kg}$.

NOTE 1 The mass of children up to 14 years is based on the anthropometric data of age group 13,5 to 14,5 years, including 2 kg for clothing. For the other age groups, the mass includes 0,5 kg, 1 kg and 1,5 kg for clothing for 4, 8 and 12 years respectively.

- b) dynamic factor

$$C_{\text{dyn}} = 1 + 1/n \quad (\text{A.2})$$

where

- C_{dyn} is a factor representing the load caused by movement (running, playing, etc.) of the users, including material behaviour under impact loading;
- n is as given in a).

c) total vertical user load

$$F_{tot;v} = g \times G_n \times C_{dyn} \quad (A.3)$$

where

$F_{tot;v}$ is the total vertical user load on the equipment caused by n children, in Newtons;

g is the acceleration due to gravity (10 m/s²);

G_n is as given in a);

C_{dyn} is as given in b).

NOTE 2 Calculated examples are given in Table A.1 for information.

Table A.1 — Total vertical load for playground intended for use by children of all ages

Number of users n	Mass of n users G_n kg	Dynamic factor C_{dyn}	Total vertical user load $F_{tot;v}$ N	Vertical load per users $F_{1,v}$ N
1	69,5	2,00	1 391	1 391
2	130	1,50	1 948	974
3	189	1,33	2 516	839
5	304	1,20	3 648	730
10	588	1,10	6 468	647
15	868	1,07	9 259	617
20	1 146	1,05	12 033	602
25	1 424	1,04	14 810	592
30	1 700	1,03	17 567	586
40	2 252	1,025	23 083	577
50	2 801	1,02	28 570	571
60	3 350	1,017	34 058	568
∞		1,00		538
NOTE At infinity the vertical load per user equals the average mass.				

d) total horizontal user load

The total horizontal user load is 10 % of the total vertical user load in accordance with A.2.2 c) and acts on the same level, together with the vertical load:

$$F_{tot;h} = 0,1F_{tot;v} \quad (A.4)$$

NOTE 3 This load allows for movement of children playing and inaccuracies in the structure.

e) distribution of user loads

The user loads are uniformly distributed over the element considered as follows:

1) point loads

$$F = F_{\text{tot}} \text{ in Newtons;} \quad (\text{A.5})$$

F is acting on an area of $0,1 \text{ m} \times 0,1 \text{ m}$;

2) line loads:

$$q = F_{\text{tot}}/L \text{ in Newtons per metre;} \quad (\text{A.6})$$

where: L is in accordance with A.3.3;

3) area loads:

$$p = F_{\text{tot}}/A \text{ in Newtons per metre squared;} \quad (\text{A.7})$$

where: A is in accordance with A.3.4;

4) volume loads:

$$q = F_{\text{tot}}/L \text{ in Newtons per metre} \quad (\text{A.8})$$

or

$$p = F_{\text{tot}}/A \text{ in Newtons per metre squared.} \quad (\text{A.9})$$

NOTE 4 Volume loads are expressed either in line loads or area loads, depending on the type of elements that form the structure.

A.2.3 Snow loads

Snow loads shall be taken from EN 1991-1-3, allowing for a reference period of 10 years.

A.2.4 Wind loads

Wind loads shall be taken from EN 1991-1-4, allowing for a reference period of 10 years.

A.2.5 Temperature loads

Temperature loads shall be taken from EN 1991-1-2, allowing for a reference period of 10 years.

A.2.6 Specific loads

A.2.6.1 Swing seats

The number of users n on a swing seat in motion shall be calculated from the following:

- a) for a traditional swing $n = 2$;
- b) for a gondola, n shall be calculated as given in A.3;
- c) for a single point swing $n = L/0,6$ with $n \geq 2$;

where

L is the total length of the outer edge of the swinging platform in metres.

The forces caused by motion of swings shall be considered for all the most onerous positions relevant for the element being considered.

The user loads in accordance with A.2.2 c) and d) need not be considered.

NOTE 1 In the case of swings, the mass can be considered as being uniformly distributed on the equipment between the points of support.

The maximum swing angle α_{\max} considered for swing seats suspended from ropes or chains is 80° from the vertical position.

NOTE 2 In Annex B the method to be used for calculating the forces resulting from the motion of a swing is included. A worked example is also given.

A.2.6.2 Carousels

The number of users on a carousel shall be the highest number calculated from:

- a) number of seats, as given in A.3.3 where L_{pr} is the total length of the seats; or
- b) platform dimensions, as given in A.3.4 where A_{pr} is the area of the platform.

For carousels, two load cases shall be considered for the user loads:

- c) the load F_{tot} is evenly distributed over the entire carousel;
- d) the load F_{tot} ($1/2 L_{pr}$ or $1/2 A_{pr}$) is evenly distributed over one half of the carousel.

NOTE Vertical and horizontal user loads act at the same time. Centrifugal forces need not be considered additionally, as they are covered by the horizontal user load.

A.2.6.3 Cableways

The maximum tension in the cable of a cableway shall be calculated for the situation where the users are swinging in a vertical direction in the middle of the cable.

The user loads as given in A.2.2 c) and d) need not be considered.

The maximum forces in the foundation of the cableway can be based on the static situation with the users in the middle of the cable.

The number of users n on a traditional cableway is $n = 2$.

NOTE In Annex B, a method that can be used for calculating the forces resulting from the motion of users suspended from a cableway is included. A worked example is also given.

A.2.6.4 Spatial networks

The number of users in a spatial network shall be calculated in accordance with A.3.5 on the basis of the volume V defined by the periphery of the spatial network.

For spatial networks two load cases shall be considered for the user loads as follows:

- a) load F_{tot} (V) is equally distributed over the entire structure;
- b) load F_{tot} ($1/2 V$) is equally distributed over one half of the structure.