

## JAPANESE INDUSTRIAL STANDARD

Translated and Published by Japanese Standards Association

 $JIS~S~2148 \tiny{:\,2013}$ 

(JIA)

Gas cylinders for portable gas cooker

 $\mathbf{ICS} \;\; 97.040.20$ 

Reference number: JISS 2148: 2013 (E)

S 2148: 2013

Date of Establishment: 1991-07-01

Date of Revision: 2013-02-20

Date of Public Notice in Official Gazette: 2013-02-20

Investigated by: Japanese Industrial Standards Committee

Standards Board

Technical Committee on Consumer Life Products

JIS S 2148: 2013, First English edition published in 2015-09

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan HN

This is a preview. Click here to purchase the full publication.

## Contents

	Page
Introduction	
1	Scope
2	Normative references ····································
3	Terms and definitions · · · · 2
4	Performance ······3
5 5.1 5.2 5.3	Filled LPG       3         Component       3         Nominal LPG volume       3         Odor       4
6	Construction ······ 4
7 7.1 7.2	Dimensions 4 Dimensions of cartridge and cartridge valve 4 Compressive (stroke) dimension and initial injection stroke dimension of cartridge valve 6
8 8.1 8.2	Material6Material of cartridge body6Material of stem7
9 9.1 9.2 9.3 9.4	Test methods 8 Test instruments and apparatus 8 Tests for construction, dimensions and materials 8 Gas resistance test 9 Ozone resistance test 9
9.5 9.6 9.7	Gas tightness test ·········9 Pressure resistance test ·········9 Stem functioning load test ·········10
9.8 9.9	Repeated use test ································
9.10 9.11	Filled LPG mass test
9.12	Test of compressive (stroke) dimension and initial injection stroke dimension of cartridge valve
<ul><li>9.13</li><li>9.14</li><li>9.15</li></ul>	Initial partial air pressure
10	Inspection