

Translated and Published by Japanese Standards Association

 $JIS \, S \, 2006 : 2016$

(JVBA/JSA)

Vacuum bottles

ICS 97.040.50

 $Reference\ number:\ JIS\ S\ 2006:2016\ (E)$

S 2006: 2016

Date of Establishment: 1953-11-07

Date of Revision: 2016-01-20

Date of Public Notice in Official Gazette: 2016-01-20

Investigated by: Japanese Industrial Standards Committee

Standards Board for ISO area

Technical Committee on Consumer Life Products

JIS S 2006:2016, First English edition published in 2016-11

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HT/AT

Contents

	Page
1	Scope
2	Normative references 1
3	Terms and definitions
44.1	Classification — 3 Classification of glass vacuum bottles — 3 Classification of stainless steel vacuum bottles — 3
5 5.1 5.2	Names of principal parts
6 6.1 6.2	Performance 9 Performance in use 9 Quality performance 9
7 7.1 7.2	Construction13General requirements13Type-specific requirements13
8	Appearance ————————————————————————————————————
9	Material
10	Test methods ·········15
$10.1 \\ 10.2 \\ 10.3$	General test conditions
$10.3 \\ 10.4 \\ 10.5$	Heat/cold insulation effect
10.6 10.7	Adhesion of print coating
10.8 10.9 10.10	Plating on plastic
10.11 10.12	Overturn angle
10.13 10.14	Outflow due to overturn
10.15 10.16 10.17	Durability of pouring mechanism

S 2006: 2016

10.18	Strength of shoulder strap	22
10.19	Colour fastness of the bag and the shoulder strap	22
10.20	Alkali elution test	22
11	Inspection method ·····	
11.1	Type inspection	23
11.2	Product inspection ·····	23
11.3	Inspection record	23
12	Marking	24
13	Instructions for use	24