



NACE SP0615 WAB Item No. 21197

Standard Practice

SSPC Surface Preparation Standard NACE WAB-2/SSPC-SP 10 (WAB) Near-White Metal Wet Abrasive Blast Cleaning

This NACE International/SSPC: The Society for Protective Coatings joint standard for qualifying and certifying industrial coating and lining application specialists represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he or she has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard practice. Nothing contained in this NACE/SSPC standard is to be construed as granting any right, by implication or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by letters patent, or as indemnifying or protecting anyone against liability for infringement of letters patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials not discussed herein. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. NACE and SSPC assume no responsibility for the interpretation or use of this standard by other parties, and accept responsibility for only those official NACE or SSPC interpretations issued by NACE or SSPC in accordance with their governing procedures and policies, which preclude the issuance of interpretations by individual volunteers.

Users of this NACE/SSPC standard are responsible for reviewing appropriate health, safety, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This NACE/SSPC standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this NACE/SSPC standard also are responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

CAUTIONARY NOTICE: NACE/SSPC joint surface preparation standards are subject to periodic review, and may be revised or withdrawn at any time in accordance with NACE/SSPC technical committee procedures. NACE and SSPC require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication and subsequently from the date of each reaffirmation or revision. The user is cautioned to obtain the latest edition. Purchasers of NACE/SSPC standards may receive current information on all standards and other NACE/SSPC joint publications by contacting the organizations at the addresses below:

ISBN 1-57590-322-9 Approved Date: 2015-03-14

NACE International 15835 Park Ten Place Houston, TX 77084-5145 +1 281-228-6200 SSPC: The Society for Protective Coatings 800 Trumbull Drive Pittsburgh, PA 15205 +1 412-281-2331

©2015, NACE International

©2015, SSPC: The Society for Protective Coatings

This is a preview. Click here to purchase the full publication.



Foreword

This NACE/SSPC joint standard defines the process for preparing a carbon steel surface to the Near-White Metal degree of surface cleanliness using a wet abrasive blast (WAB) method of cleaning. This standard is intended for use by coating or lining specifiers, applicators, inspectors, or others whose responsibility is to define a standard degree of surface cleanliness for carbon steel surfaces to be achieved by wet abrasive blast cleaning.

| Degree of Surface Cleanliness | Designation |
|-------------------------------|--|
| White Metal WAB | NACE WAB-1/SSPC-SP 5 (WAB) ¹ |
| Near-White Metal WAB | NACE WAB-2/SSPC-SP 10 (WAB) |
| Commercial WAB | NACE WAB-3/SSPC-SP 6 (WAB) ² |
| Industrial WAB | NACE WAB-8/SSPC-SP 14 (WAB) ³ |
| Brush-Off WAB | NACE WAB-4/SSPC-SP 7 (WAB) ⁴ |

WAB cleaning is a process using a mixture of water and abrasive that can produce various levels of surface cleanliness and surface profile (roughness) similar to those obtained with dry abrasive blast (DAB) cleaning. WAB cleaning may be specified when dust suppression is desired, and may also be a means for reducing soluble salt contamination. The WAB cleanliness level specified should be the same as the corresponding degree of cleaning specified if DAB cleaning were the process being used.

The focus of this standard is Near-White Metal WAB cleaning. The five degrees of WAB cleaning are as follows:

Near-White Metal WAB cleaning provides a greater degree of cleaning than Commercial WAB cleaning (NACE WAB-3/SSPC-SP 6 [WAB]) but less than White Metal WAB cleaning (NACE WAB 1/SSPC- SP 5 [WAB]).

Near-White Metal WAB cleaning is used when the objective is to remove all rust and other corrosion products, coating, and mill scale, but when the extra effort required to remove all stains of these materials is determined to be unwarranted.

Near-White Metal WAB cleaning allows staining on no more than 5% of each unit area of surface, while commercial WAB cleaning allows staining on no more than 33% of each unit area of surface. White Metal WAB cleaning does not permit any staining to remain on the surface.

This standard references the three levels of flash rust as defined in the NACE/SSPC joint standards for waterjetting (see Paragraph 3.1 in this standard).⁵⁻⁸ Nonmandatory Appendixes A, B, and C offer additional information regarding flash rust.

Steel surfaces prepared by WAB cleaning can develop flash rust within minutes after the cleaning is completed. The project specification often contains requirements for the permissible level of flash rust before coating application (Additional information is provided in Appendix A, Paragraph A1 and Appendix C.)

NACE International i